

Serial No. 09/753,371  
October 17, 2003  
Response to Office Action of May 22, 2003  
Page 2 of 11

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**LISTING OF CLAIMS:**

C

Claim 1 (currently amended): An angular velocity sensor comprising:  
a substrate;  
an oscillator disposed on the substrate so as to be displaceable relative to the substrate; and  
an impact damping mechanism disposed on the substrate for dampening damping the effect on oscillations of the oscillator from an impact to the substrate;  
a frame for supporting the oscillator;  
a support member for supporting the frame;  
an oscillator support beam connecting the oscillator to the frame; wherein  
said impact damping mechanism is defined by a single unitary member including a portion for damping in a Y-direction and a portion for damping in an X-direction which is substantially perpendicular to the Y-direction; and  
said single unitary member connects the frame with the support member.

Claim 2 (previously presented): An angular velocity sensor comprising:  
a substrate;  
an impact damping mechanism disposed on the substrate for damping an impact applied to the substrate;  
an oscillator supported on the substrate by at least one oscillator support beam, so as to be displaceable in two directions that are substantially parallel to the substrate and substantially orthogonal to each other;  
an oscillation-generating mechanism for oscillating the oscillator in an oscillating direction that is substantially parallel to one of the two directions; and

C

Serial No. 09/753,371

October 17, 2003

Response to Office Action of May 22, 2003

Page 3 of 11

an angular-velocity detecting mechanism for detecting a displacement of the oscillator as an angular velocity when the oscillator is displaced in a detecting direction that is substantially orthogonal to the oscillating direction,

wherein the impact damping mechanism damps an impact to the substrate along at least one direction of the oscillating direction and the detecting direction so as to prevent the impact from being transferred to the oscillator from the substrate;

the impact damping mechanism includes a frame support beam disposed on the substrate and a frame supported on the substrate by the frame support beam so as to be displaceable in at least one of the oscillating direction and the detecting direction, and wherein the oscillator is supported on the inside of the frame via the oscillator support beam such as to be displaceable in both of the oscillating direction and the detecting direction; and

the substrate is provided with a support section arranged outside the frame so as to surround the frame for supporting the frame via the frame support beam and wherein the impact damping mechanism includes a damping clearance portion arranged between the support section and the frame for compressing a gas when the frame is displaced.

Claim 3 (canceled)

Claim <sup>3</sup>~~4~~ (previously presented) An angular velocity sensor comprising:  
a substrate;

an impact damping mechanism disposed on the substrate for damping an impact applied to the substrate;

an oscillator supported on the substrate by at least one oscillator support beam, so as to be displaceable in two directions that are substantially parallel to the substrate and substantially orthogonal to each other;

Serial No. 09/753,371

October 17, 2003

Response to Office Action of May 22, 2003

Page 4 of 11

an oscillation-generating mechanism for oscillating the oscillator in an oscillating direction that is substantially parallel to one of the two directions; and

an angular-velocity detecting mechanism for detecting a displacement of the oscillator as an angular velocity when the oscillator is displaced in a detecting direction that is substantially orthogonal to the oscillating direction,

wherein the impact damping mechanism damps an impact to the substrate along at least one direction of the oscillating direction and the detecting direction so as to prevent the impact from being transferred to the oscillator from the substrate;

the impact damping mechanism includes a frame support beam disposed on the substrate and a frame supported on the substrate by the frame support beam so as to be displaceable in at least one of the oscillating direction and the detecting direction, and wherein the oscillator is supported on the inside of the frame via the oscillator support beam so as to be displaceable in both of the oscillating direction and the detecting direction; and

the oscillator, the oscillator support beam, and the frame have an entire resonant frequency which is set to be about  $1/\sqrt{2}$  times more than or less than a resonant frequency of the oscillator.

Claim <sup>4</sup>~~5~~ (previously presented): An angular velocity sensor according to claim <sup>3</sup>~~4~~, wherein the substrate is provided with a support section arranged outside the frame so as to surround the frame for supporting the frame via the frame support beam and wherein the impact damping mechanism includes a damping clearance portion arranged between the support section and the frame for compressing a gas when the frame is displaced.

Claim 6 (previously presented): An angular velocity sensor according to any one of claims 1, 2 or <sup>3</sup>~~4~~, wherein the oscillator is formed to be displaceable in an oscillating direction parallel to the substrate and in a detecting direction orthogonal to the

Serial No. 09/753,371

October 17, 2003

Response to Office Action of May 22, 2003

Page 5 of 11

substrate, and wherein the impact damping mechanism is formed so as to damp an impact in the oscillating direction and to prevent the impact from being transferred to the oscillator from the substrate.

C1  
(contd)

Claim ~~7~~<sup>8</sup> (previously presented): An angular velocity sensor according to any one of claims 1, 2 or ~~4~~<sup>3</sup>, wherein the oscillator is formed to be displaceable in oscillating and detecting directions parallel to the substrate and orthogonal to each other, and wherein the impact damping mechanism is formed so as to damp an impact in at least one direction of the oscillating and detecting directions and to prevent the impact from being transferred to the oscillator from the substrate.

Claim ~~8~~<sup>10</sup> (previously presented): An angular velocity sensor according to any one of claims 1, 2 or ~~4~~<sup>3</sup>, wherein the oscillator, the oscillator support beam, and the impact damping mechanism are unitarily formed by a single-crystalline or polycrystalline silicon material.

Claim ~~9~~<sup>5</sup> (previously presented): An angular velocity sensor according to claim ~~5~~<sup>4</sup>, wherein the oscillator, the oscillator support beam, and the impact damping mechanism are unitarily formed by a single-crystalline or polycrystalline silicon material.

Claim ~~10~~<sup>7</sup> (previously presented): An angular velocity sensor according to claim 6, wherein the oscillator, the oscillator support beam, and the impact damping mechanism are unitarily formed by a single-crystalline or polycrystalline silicon material.

Claim ~~11~~<sup>9</sup> (previously presented): An angular velocity sensor according to claim ~~7~~<sup>8</sup>, wherein the oscillator, the oscillator support beam, and the impact damping mechanism are unitarily formed by a single-crystalline or polycrystalline silicon material.

C

10/17/2003 16:44

7033855080

KEATING & BENNETT

PAGE 07/14

Serial No. 09/753,371

October 17, 2003

Response to Office Action of May 22, 2003

Page 6 of 11

*C1  
(encl.)* Claim 12 (canceled)

---